



NOTES:

1. FORMAT: SECURE ENGINEER'S APPROVAL OF SIGN FORMAT AND INSTALLATION
2. INSTALLATION:
 - A. INSTALL SIGNS ON THE NORTH-EAST OR SOUTH-WEST CORNERS OF THE INTERSECTION.
 - B. INSTALL THE EDGE OF THE SIGN 2 FEET FROM THE VERTICAL EXTENSION OF THE BACK OF CURB AS NEAR AS POSSIBLE TO THE APPROACH CURB P.C. (POINT OF CURVATURE).
3. NAMED STREETS SHOULD ALSO INCLUDE NUMERIC LOCATION ON RIGHT SIDE OF SIGN

STREET NAME SIGNS:

1. SIZE 38" X 8"
2. DOUBLE BLADED .080 ALUMINUM WITH RIVETED ENDS AND BACK WASHERS
3. 6" C SERIES UPPER CASE LETTERS FOR MAIN TEXT
4. 3" C SERIES UPPER CASE LETTERS IF COORDINATE IS REQUIRED
5. SUPER ENGINEER GRADE LETTERING ON PRISMATIC GRADE GREEN BACKGROUND
6. 8" X 8" LOGO LEFT HAND PORTION OF SIGN
7. LOGO COLOR: BLUE AND GOLD ON ENGINEER GRADE WHITE
8. LOGO LETTERING "HEBER CITY" W/ HEBER CITY OFFICE BUILDING IN TRIPLICATE FADING INTO BACKGROUND

REGULATORY SIGNS:

1. ALL STOP (R1-1-30), YIELD (R1-2-36) & SPEED LIMIT (R2-1-24) SIGNS ARE .080 ALUMINUM WITH PRISMATIC REFLECTIVE SHEETING
2. ALL OTHER SIGNS .080 ALUMINUM W/ PRISMATIC GRADE SHEETING

STREET ADDRESS SIGNS

N.T.S.

HEBER CITY
STANDARD DRAWING
STREETS-10