



REQUIRED SLOPE TABLE		
LOCATION	RUNNING SLOPE	CROSS SLOPE
C	5% MAX	2% MAX *
F	25% MAX (SEE NOTE 3)	-
R	5.1% MIN TO 8.3% MAX	2% MAX *
T	2% MAX	2% MAX *
SW	-	2% MAX

* DO NOT EXCEED THE ROADWAY PROFILE GRADE FOR THE CROSS SLOPE AT LOCATIONS WITHOUT A STOP OR YIELD SIGN OR AT MID-BLOCK RAMPS.

NOTES:

1. RAMP TO INCLUDE ADA DETECTABLE WARNING STRIP; IE. ADA SOLUTIONS, ARMOR-TILE CAST-IN-PLACE, MASCO CASTINTACT, WAUSAU, OR TEKWAY.
2. COLOR OF ADA DETECTABLE WARNING STRIP SHALL BE DARK RED OR GRAY.
3. CURB TAPER SLOPE FOR FLARES SHALL BE 10% MAXIMUM IF IT FALLS WITHIN THE PEDESTRIAN ACCESS ROUTE AS DEFINED BY UDOT.
4. NO LIPS ALLOWED. AT THE CURB CUT, A LIP IS A VERTICAL DISCONTINUITY GREATER THAN 1/4". AT THE GUTTER/ROAD TRANSITION, A LIP IS A VERTICAL DISCONTINUITY GREATER THAN 1/2". VERTICAL DISCONTINUITIES GREATER THAN 1/4" SHALL BE BEVELED WITH A SLOPE NOT GREATER THAN 50%.
5. ALL PEDESTRIAN RAMPS ARE SUBJECT TO THE REQUIREMENTS SHOWN ON THE UDOT PEDESTRIAN ACCESS STANDARD DRAWINGS. WHERE CONFLICTS EXIST, THE MORE STRINGENT SHALL GOVERN.

MID-BLOCK PEDESTRIAN RAMPS

V:\ENGR\Stus\StusSpec\StusSpec 2019\Drawg Files\STREET6.dwg - ADA Ramp - 2/06/2019 11:49am - rfunk

<p>728 WEST 100 SOUTH #2 HEBER CITY, UTAH 84032 (435) 654-2226</p>	DATE: FEBRUARY 2019 SCALE: N.T.S.		<p>HEBER CITY STANDARD DRAWING</p> <p>STREETS-6</p>
	75 NORTH MAIN STREET HEBER CITY, UTAH 84032 (435) 654-0757		