

NOTES:

1. WHEREVER POSSIBLE, SANITARY SEWER SHALL BE INSTALLED ON THE DOWNHILL SIDE OF THE STREET.
2. SUBGRADE SHALL BE A-1 GRANULAR MATERIAL PER SECTION 02225.
3. COMMERCIAL SIDEWALK TO BE FIVE FEET WIDE MINIMUM.
4. MAXIMUM ROAD GRADE IS 8% WITHOUT CITY ENGINEER'S APPROVAL.
5. PARK STRIPS TO BE FILLED TO WITHIN ONE INCH OF T.B.C. AND TOP OF SIDEWALK


STREET CROSS-SECTIONS AND UTILITY LOCATIONS

V:\ENGR\Stus\StusSpec\StusSpec 2019\Drawg Files\STREETS-2.dwg - XSec-Minor Major Coll. - 2/06/2019 11:41am. r.funk

HORROCKS
ENGINEERS

728 WEST 100 SOUTH #2
HEBER CITY, UTAH 84032
(435) 654-2226

DATE:	FEBRUARY 2019
SCALE:	N.T.S.
75 NORTH MAIN STREET HEBER CITY, UTAH 84032 (435) 654-0757	



**HEBER CITY
STANDARD DRAWING**

STREETS-2